

# Stratasys® J35™ Pro

The Stratasys® J35™ Pro 3D printer combines the quality of Stratasys PolyJet technology with a compact, office-friendly design.

The three material channel, multi material printer features a rotating build platform with fixed print head for outstanding surface finish and print quality. Engineered for the office or design studio environment, it features a small footprint and ProAero™ filtration technology for odor free, silent and low power operation.

The J35 Pro offers a streamlined design-to-print workflow powered by GrabCAD Print™. This allows users to import their designs using native CAD files or 3MF file formats.

Remote monitoring lets you easily manage your print jobs from outside the office. Additionally, hands-free soluble support removal makes post processing simple and enables the creation of complex parts without compromising accuracy or detail.

## Product Specifications

Model Materials	<ul style="list-style-type: none"> <li>• VeroUltra™ ClearS</li> <li>• VeroUltra™ BlackS</li> <li>• VeroUltra™ WhiteS</li> </ul>	<ul style="list-style-type: none"> <li>• Vero™ ContactClear</li> <li>• DraftGray™</li> <li>• D-ABS Plus™</li> </ul>	<ul style="list-style-type: none"> <li>• Elastico™ Black</li> <li>• Elastico™ Clear</li> </ul>
Support Materials	SUP710™		
Build Size/Printing Area	Round Print Tray with up to 1,174cm <sup>2</sup> (182 in <sup>2</sup> ) Print Height: 158mm* (6.22 in.)* Maximum model height: 155 mm (6.1 in.)		
Layer Thickness	Horizontal build layers down to 18 microns (0.0007 in.)		
Network Connectivity	LAN - TCP/IP		
System Size and Weight	651 x 661 x 774mm* (25.63 x 26.02 x 30.48 in.); 98 kg (216 lbs.)		
Operating Conditions	Temperature 18 – 25 °C (64 – 77 °F); relative humidity 30-70% (non-condensing)		
Power Requirements	100–240 VAC, 50–60 Hz, 10A, 1 phase		
Regulatory Compliance	CE, FCC, EAC, cTUVus, CB		
Software	GrabCAD Print		
Build Modes	High Quality Speed (HQS) – 18.75um		
Accuracy	Deviation from STL dimensions, for 1 Sigma (67%) of models printed with rigid materials, based on size: under 100 mm – ±150µ; above 100 mm – ±0.15% of part length.** Deviation from STL dimensions, for 2 Sigma (95%) of models printed with rigid materials, based on size: under 100 mm – ±180µ; above 100 mm – ±0.2% of part length.**		
Additional features	<ul style="list-style-type: none"> <li>• Long Print Mode (allowing cartridge Hot Swap for selected material)</li> <li>• Notifications for user via email and GC APP</li> <li>• Internal camera</li> <li>• VoxelPrint (per order)</li> </ul>		

\* The printable height is 158 mm (6.22 in.) and the max printable model height is 155 mm (6.1 in.).

\*\* Measured when ambient temperature is 23 °C and relative humidity is 50%.



### VARINEX Zrt.

1106 Budapest, Fehér út 10.  
+361 432 0248  
3DP@varinex.hu  
varinex.hu

[stratasys.com](http://stratasys.com)

ISO 9001:2015 Certified

