

# J850™ TechStyle™

## Product Specifications

- Model Materials**
- Vero™ & VeroUltra™ family of opaque materials + neutral shades and vibrant VeroVivid™ colors
  - Agilus30™ Clear, Black, White, Cyan, Magenta, Yellow
  - Transparent VeroClear™ and VeroUltra™ Clear
  - Vero™ContactFlex for soft touch model coating

- Digital Model Materials**
- Unlimited number of digital materials including:**
- Over 600,000 colors and Pantone® Validated palettes
  - Translucent color tints
  - Flexible tactile materials in a variety of textures and colors

- Support Materials**
- SUP705™ (water jet removable)  
SUP706B™ (soluble)

ISO standards	100% Cotton	100% Polyester	50/50% Cotton Polyester	Linen
Color Fastness to Laundering @40c - ISO 105-C06:2010 (1-5)	5	5	5	5
Color Fastness to Laundering @60c - ISO 105-C06:2010 (1-5)	5	5	5	5
Color Fastness to Light ISO 105-B02:2013 (1-8)	7-8	7-8	7-8	7-8

- Build Size**
- Fabric Size Handling:** min 560 x 460mm; max 2 x 2m  
**Fabric Thickness:** 0.1-3.0mm  
Interchangeable Tray for smooth production runs

**Effective Printing Area** 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fabric up to 2m<sup>2</sup>

**Layer Thickness** Horizontal build layers down to 27-micron (0.001 in.)

**Workstation Compatibility** Windows 10

**Network Connectivity** LAN - TCP/IP  
Industry 4.0 Compliance

- System Size and Weight**
- J850 TechStyle System:**  
1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (948 lbs.)  
**J850 TechStyle Material Cabinet:**  
1119 x 656 x 637 mm (44 x 25.8 x 25.1 in.); 153 kg (337 lbs.)

\*Test results based on 50 x 50 cm textile samples comprising 3D printed elements of various colors.

# J850™ TechStyle™

## Product Specifications

Operating Conditions	Temperature 18 – 25 °C (64 – 77 °F); relative humidity 30-70% (non-condensing)
Power Requirements	100–120 VAC, 50–60 Hz, 13.5 A, 1 phase; 220–240 VAC, 50–60 Hz, 7 A, 1 phase
Regulatory Compliance	CE, FCC, EAC, RCM, R-NZ1
Software	GrabCAD Print, SDK (API)
Build Modes	<b>High Mix:</b> up to 7 base resins, 27-micron (0.001 in.) resolution <b>High Speed:</b> up to 3 base resins, 27-micron (0.001 in.) resolution

### J850 TechStyle System:

Typical deviation from STL dimensions, for models printed with rigid materials, based on size: under 100 mm –  $\pm 100\mu$ ; above 100 mm –  $\pm 200\mu$  or  $\pm 0.06\%$  of part length, whichever is greater.

**Print on Existing Patterns:** up to 1mm

Accuracy

### Software:

Deviation from STL dimensions, for 1 Sigma (67%) of models printed with rigid materials, based on size: under 100 mm –  $\pm 150\mu$ ; above 100 mm –  $\pm 0.15\%$  of part length.

Deviation from STL dimensions, for 2 Sigma (95%) of models printed with rigid materials, based on size: under 100 mm –  $\pm 180\mu$ ; above 100 mm –  $\pm 0.2\%$  of part length.



**VARINEX Zrt,**

1106 Budapest, Fehér út 10.

+361 432 0248

3DP@varinex.hu

varinex.hu

[stratasys.com](https://stratasys.com)

ISO 9001:2015 Certified

© 2022 Stratasys Ltd. All rights reserved. Stratasys, Stratasys signet J850, TechStyle, 3DFashion, GrabCAD Print, Vero, VeroVivid, Agilus30, VeroClear, VeroUltraClear, VeroContactFlex SUP710, SUP705 and SUP706B, are trademarks or registered trademarks of Stratasys Ltd. and/or its subsidiaries or affiliates and may be registered in certain jurisdictions. PANTONE® and other Pantone trademarks are the property of Pantone LLC. Pantone's trademarks and copyrights used with the permission of Pantone LLC under License Agreement with Stratasys Ltd. All other trademarks belong to their respective owners. Product specifications subject to change without notice. PSS\_PJ\_TechStyle\_0322a

